



# ComColor 7150

*Speed up your color communications  
to boost up your business*



---

A3/Ledger

---

120 ppm

---

Multiple Paper Trays

# ComColor 7150

## Specifications

<b>Print Type</b>	Line-type inkjet system	
<b>Ink Type</b>	Oil-based pigment ink (Cyan, Magenta, Yellow, Black)	
<b>Resolution</b>	Standard: 300 dpi (main scanning direction) × 300 dpi (subscanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (subscanning direction)	
<b>Number of Gray Levels</b>	For each CMYK color (8 gray levels)	
<b>Data Processing Resolution</b>	Standard: 300 dpi × 300 dpi Fine: 300 dpi × 600 dpi Line smoothing: 600 dpi × 600 dpi	
<b>Warm-up Time</b>	2 min. 45 sec. or less (at room temperature of 20°C (68°F))	
<b>First Print Time</b>	5 sec. or less <sup>1</sup> (when copying A4/Letter long-edge feed using color mode)	
<b>Continuous Print Speed<sup>2,6</sup></b>	<b>A4 long-edge feed</b>	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)
	<b>Letter long-edge feed</b>	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)
	<b>A4 short-edge feed</b>	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)
	<b>Letter short-edge feed</b>	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)
	<b>B4/Legal short-edge feed</b>	Simplex: 76 ppm, Duplex: 38 sheets/minute (76 ppm)
	<b>A3 short-edge feed</b>	Simplex: 66 ppm, Duplex: 33 sheets/minute (66 ppm)
	<b>Ledger short-edge feed</b>	Simplex: 66 ppm, Duplex: 33 sheets/minute (66 ppm)
<b>Paper Size</b>	<b>Standard Tray</b>	Maximum: 340 mm × 550 mm (13 3/8" × 21 5/8") Minimum: 90 mm × 148 mm (3 9/16" × 5 13/16")
	<b>Feed Tray</b>	Maximum: 297 mm × 420 mm (11 11/16" × 17") Minimum: 182 mm × 182 mm (7 3/16" × 7 3/16")
<b>Printable Area</b>	Maximum: 314 mm × 548 mm (12 3/8" × 21 9/16")	
<b>Guaranteed Print Area<sup>3</sup></b>	Standard: Margin width of 3 mm (1/8") Maximum: Margin width of 1 mm (0.04")	
<b>Paper Weight</b>	<b>Standard Tray</b>	46 gsm (12-lb bond) to 210 gsm (56-lb bond) (plain paper)
	<b>Feed Tray</b>	52 gsm (14-lb bond) to 104 gsm (28-lb bond) (plain paper)
<b>Paper Feed Method/ Paper Tray Capacity</b>	<b>Standard Tray</b>	Height up to 110 mm (4 5/16")
	<b>Feed Tray</b>	Height up to 50 mm (1 15/16") (× 3 trays)
<b>Output Tray Capacity</b>	<b>Standard</b>	Height up to 60 mm (2 3/8")
<b>Page Description Language</b>	RISORINC/CIII	
<b>Supported Protocols</b>	TCP/IP, HTTP, HTTPS (SSL), DHCP, ftp, lpr, IPP, SNMP, Port 9100 (RAW port), IPv4, IPv6, IPsec	
<b>Supported Operating Systems</b>	Microsoft® Windows® XP (32-bit), Microsoft® Windows Server® 2003 (32-bit/64-bit), Microsoft® Windows Server® 2003 R2 (32-bit/64-bit), Microsoft® Windows Vista® (32-bit/64-bit), Microsoft® Windows Server® 2008 (32-bit/64-bit), Microsoft® Windows Server® 2008 R2 (64-bit), Microsoft® Windows® 7 (32-bit/64-bit), Microsoft® Windows® 8 (32-bit/64-bit) <sup>8</sup> , Microsoft® Windows Server® 2012 (64-bit) <sup>8</sup>	
<b>Network Interface</b>	Ethernet 1000BASE-T, 1000BASE-TX, 10BASE-T	
<b>Memory Capacity</b>	1 GB	
<b>Hard Disk<sup>4</sup></b>	<b>Capacity</b>	320 GB
	<b>Available Space</b>	280 GB
<b>Operating System</b>	Linux	
<b>Power Source</b>	AC 100-240 V, 10-5 A, 50-60 Hz	
<b>Power Consumption</b>	Maximum: 1,000 W Ready <sup>5</sup> : 150 W or less Sleep <sup>7</sup> : 5 W or less Stand-by: 0.5 W or less	
<b>Operating Noise</b>	Max. 66 dB (when printing without optional equipment connected)	
<b>Operating Environment</b>	Temperature: 15°C to 30°C (59°F to 86°F) Humidity: 40% to 70% RH (non-condensing)	
<b>Dimensions (W × D × H)</b>	In use: 1,220 mm × 705 mm × 1,030 mm (48 1/32" × 27 3/4" × 40 9/16") Cover and feed trays closed: 1,155 mm × 705 mm × 1,010 mm (45 15/32" × 27 3/4" × 39 3/4")	
<b>Required Space (W × D × H)</b>	Cover and feed trays opened: 1,220 mm × 1,240 mm × 1,030 mm (48 1/32" × 48 13/16" × 40 9/16")	
<b>Weight</b>	Approx. 171 kg (376 lb)	

<sup>1</sup> Within 10 minutes after the last print job

<sup>2</sup> When using plain paper and recycled paper (85 gsm (23-lb bond)), and density setting 3 (Standard) Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)]

<sup>3</sup> The margin when printing envelopes is 10 mm (3/8"). The guaranteed area when printing images is the area enclosed within 3 mm (1/8") of the edges of the paper.

<sup>4</sup> One gigabyte (GB) is calculated as one billion bytes.

<sup>5</sup> Without printing and temperature adjustment operation

<sup>6</sup> The continuous print speed varies depending on the type of optional output equipment connected. Multifunction finisher: Max. 120 sheets/minute (A4 long-edge feed simplex) Face down offset stapler: ComColor 7150: Max. 120 sheets/minute (A4 long-edge feed simplex)

<sup>7</sup> When setting [Power consumption (in sleep)] to [Low].

<sup>8</sup> Will soon be compatible, however will remain incompatible with Microsoft® Windows® RT.

RISO logo, ComColor, ComColorExpress, and FORCEJET are trademarks or registered trademarks of Riso Kagaku Corporation. Adobe and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Mac is a trademark of Apple Inc. Microsoft, Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, Pentium and Xeon are trademarks of Intel Corporation in the United States and/or other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



**RISO KAGAKU CORPORATION**  
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan  
<http://www.riso.com>

**COPYLANDIA**  
Office Systems Corporation  
718 Bumtay Street, Mandaluyong City 1550  
**CALL 535-8-535** [www.copylandia.com](http://www.copylandia.com)